

SW-4, 26 DEC 2024 to 23 JAN 2025

PHOENIX DEP CON
119.2 281.45
D-ATIS
127.575
CLNC DEL
118.1 269.2
CPDLC
GND CON
119.75 269.2 (NORTH)
132.55 269.2 (SOUTH)
PHOENIX TOWER
118.7 278.8 (Rwy 8-26)
120.9 254.3 (Rwys 7L-25R, 7R-25L)

TAKEOFF MINIMUMS

Rwys 7L, 7R, 8: Standard with minimum climb of 350' per NM to 8000.
Rwys 25L, 25R, 26: Standard with minimum climb of 350' per NM to 8000.

**TOP ALTITUDE:
8000**


R-240
ALBUQUERQUE
113.2 ABQ
Chan 79

12000
*11100
059°
(12.1)

J18
V190
R-326
ST JOHNS
112.3 SJN
Chan 70

J18
V190
054°
(11.5)

PHOENIX
115.6 PXR
Chan 103



NOTE: Restricted to turbojet and turboprop aircraft only.

NOTE: RADAR and DME required.

NOTE: Aircraft filing over ACH, LBL, ONM, CNX, PNH, MMB, TCC, IRW and TXO file BALDY DEPARTURE.

NOTE: Aircraft filing over CIM, FTI and GCK file ST JOHNS DEPARTURE.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SW-4, 26 DEC 2024 to 23 JAN 2025