

WAAS CH 63212 W18B	APP CRS 185°	Rwy Idg 12004 TDZE 94 Apt Elev 96
--	------------------------	--

RNAV (GPS) RWY 18R

ORLANDO INTL (MCO)


RNP APCH - GPS

▼ LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C.




MISSED APPROACH: Climb to 500 then climbing right turn to 4000 direct CAMBE and hold, continue climb-in-hold to 4000.

D-ATIS ARR 121.25 DEP 120.525	ORLANDO APP CON 124.8 307.0	ORLANDO TOWER 118.45 253.5 (Rwys 17L-35R, 17R-35L) 124.3 253.5 (Rwys 18L-36R, 18R-36L)	GND CON 126.4 (East) 121.8 (West)	CLNC DEL 134.7 341.7	CPDLC
---	---------------------------------------	--	---	--	-------



ELEV 96	D	TDZE 94
----------------	----------	----------------



HOLOP	NAVAL	ONNER	HAMMY	TUFFE	RWY 18R
5000	4000	3000	3000	2200	
GP 3.00° TCH 55		3.2 NM		3.2 NM	2.5 NM
		5.2 NM		1.2 NM	
1.2 NM to RWY 18R					

HIRL all Rwys	REIL Rwy 36L
TDZ/CL Rwys 17L/R, 18R, 35L/R and 36R	

CATEGORY	A	B	C	D
LPV DA		294/18	200 (200-½)	
LNAV/VNAV DA		390/24	296 (300-½)	
LNAV MDA	540/24	446 (500-½)	540/45	446 (500-¾)
C CIRCLING	740-1	644 (700-1)	740-1¾ 644 (700-1¾)	740-2 644 (700-2)

SE-3, 26 DEC 2024 to 23 JAN 2025

SE-3, 26 DEC 2024 to 23 JAN 2025