ILS or LOC RWY 24

NORTHEAST ALABAMA RGNL (GAD)

LOC/DME I-GAD	APP CRS	Rwy Idg	6802
108.35	244°	TDZE	560
Chan 20 (Y)		Apt Elev	569

DME required. VDP NA when using Anniston altimeter setting. When local altimeter setting not received, use Anniston altimeter setting and increase DA to 845 feet and all visibilities ¼ SM: increase all MDAs 80 feet and visibility S-LOC Cats C and D ¼ SM and Circling Cat C ½ SM.

MISSED APPROACH: Climb to 3600 on GAD VOR/DME R-231 to STAMP/GAD 10 DME and hold, continue climb-in-hold to 3600.

AWOS-3PT	BIRMINGHAM APP CON	CLNC DEL	UNICOM
127.825	125.45 279.65	120.05 257.7	122.8 (CTAF) L

ALTERNATE MISSED APCH FIX

114.4 VUZ Chan 91 — 067° — 247° — R-067 — STAMP VUZ 35.1

DME REQUIRED

(IAF) EBAZE GAD 23.1

3600 NoPT to HUBJU 184° hdg (8.7) and 244° (4.4)

GAD R-059

1949 1399

(IF/IAF) HUBJU I-GAD 14.4

064° — 1 min — 244° — (CFRZN)

FIKOX I-GAD 10.2

1277

3600 to HUBJU 059° (13.1)

WANEB I-GAD 4.6

991 991 1196 1280

GADSDEN 112.3 GAD Chan 70

2500 — 244° — 3000 — (4.2) — (2.9) — LR-069

GAD 13.1 Arc — 3600 NoPT

MSA GAD 25 NM — 3400

1208 735 825 804

BLKEY I-GAD 7.3

1757

R-089

(IAF) MAYES GAD 13.1

710 1135 1495 1316

1749

R-231 — 051° — 231°

STAMP GAD 10

LOCALIZER 108.35 I-GAD Chan 20(Y)

ELEV 569 | TDZE 560

244° 6 NM from FAF

8L — 4806 X 100 — 6802 X 150 — 0.3% UP — 36 — 603

3600 | GAD R-231 | STAMP

Use I-GAD DME when on the localizer course.

*LOC only.

HUBJU I-GAD 14.4 — FIKOX I-GAD 10.2 — BLKEY I-GAD 7.3 — WANEB I-GAD 4.6 2500 — *I-GAD 3 — I-GAD 1.3

One Minute Holding Pattern

064° → 3600 — 244° ← 244° — 3000

1620* — 2500

GS 3.00° TCH 43

1.7 NM — 1.6 NM — 2.7 NM — 2.9 NM — 4.2 NM

CATEGORY	A	B	C	D
S-ILS 24	779-¾ 219 (300-¾)			
S-LOC 24	1140-1 580 (600-1)		1140-1¾ 580 (600-1¾)	
C CIRCLING	1140-1 571 (600-1)		1440-2½ 871 (900-2½)	1680-3 1111 (1200-3)

HIRL Rwy 6-24 L
MIRL Rwy 18-36 L
REIL Rwys 6 and 24 L

SE-4, 26 DEC 2024 to 23 JAN 2025
SE-4, 26 DEC 2024 to 23 JAN 2025