LOC RWY 35

OUTLAW FLD (CKV)

LOC I-CKV	APP CRS	Rwy Idg	5999
111.7	347°	TDZE	550
		Apt Elev	550

ADF required.
RADAR required.

Circling NA W of Rwy 17-35. Circling Rwy 5, 17, 23 NA at night. Rwy 35 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Campbell AAF (Fort Campbell) altimeter setting. * DME from CKV VOR/DME.

MALS

MISSED APPROACH: Climb to 1800 then climbing right turn to 2200 direct CKV VOR/DME and hold.

ASOS	CAMPBELL APP CON	UNICOM
134.575	134.35 307.025	122.8 (CTAF) L



ELEV 550 D TDZE 550



FAF to MAP 5.3 NM

Knots	60	90	120	150	180
Min:Sec	5:18	3:32	2:39	2:07	1:46



CATEGORY	A	B	C	D
S-LOC 35	1080-¾ 530 (600-¾)		1080-1¼ 530 (600-1¼)	
C CIRCLING	1080-1 530 (600-1)		1080-1½ 530 (600-1½)	1200-2 650 (700-2)
	YORUK FIX MINIMUMS * (DME REQUIRED)			
S-LOC 35	880-¾ 330 (400-¾)			
C CIRCLING	1000-1 450 (500-1)	1020-1 470 (500-1)	1020-1½ 470 (500-1½)	1200-2 650 (700-2)

SE-1, 26 DEC 2024 to 23 JAN 2025
SE-1, 26 DEC 2024 to 23 JAN 2025