ATIS★ 118.6
CLNC DEL 124.8
GND CON 121.6
SCOTTSDALE TOWER★ 119.9 (CTAF)
PHOENIX DEP CON 120.7 239.0
ALBUQUERQUE 113.2 ABQ Chan 79
ST. JOHNS 112.3 SJN Chan 70
BLYTHE 117.4 BLH Chan 121
BUCKEYE 110.6 BXK Chan 43
GILA BEND 116.6 GBN Chan 113
PHOENIX 115.6 PXR Chan 103
STANFIELD 114.8 TFD Chan 95
TUCSON 116.0 TUS Chan 107
ACOMA
L-8, H-4
13000
*11100
055°
(90)
R-240
(31)
J18
V190
R-236
(115)
V190
J18
J92
FORPE
86
67
38
JONHH
25
250°
285°
321°
13000
*12000
054°
R-054
R-206
R-321
PHOENIX
8000
*5200
163°
WINRR
R-343
(14)
R-288
22
MOBIE
11000
*6600
206°
R-042
5500
*5300
257°
R-077
V16
V16
11000
*6600
235°
(120)
R-055
5900
*5900
262°
(98)
54
44
R-080
Approximate distance from Take-off area to JONHH, 18 NM.
N
NOTE: DME required.
NOTE: RADAR required.
NOTE: Restricted to turbojet and turboprop aircraft only.
NOTE: Turbojets landing LAX file J4 after BXK.
NOTE: Aircraft landing other than LAX, and turboprops landing LAX requesting FL240 and above, file J212 after BXK.
NOTE: Aircraft filing via SJN, ABQ, LVS, CIM, or GCK use ABQ transition.
NOTE: Aircraft filing south of LVS, via TCC, PNH, LBL, GAG, or TXO use SCOTTSDALE DEPARTURE.
NOTE: BLYTHE transition restricted to aircraft requesting FL220 and below.
NOTE: All transitions require RADAR vectors from over JONHH.
8000
*5200
163°
(14)
8000
*6700
133°
(24)
J92
V105
BASER
8000
*6700
115°
(6)
15000
*10000
107°
(59)
8000
*6700
121°
(69)
PUSCH
FL180
*11400
107°
(41)
OLLIN
100
40
R-295
R-301
DINGO
NOTE: Chart not to scale.
TAKEOFF MINIMUMS
Rwy 3: Standard with minimum climb of 440' per NM to 4000.
Rwy 21: Standard with minimum climb of 215' per NM to 4000.
(CONTINUED ON FOLLOWING PAGE)