

WAAS CH 45639 W01A	APP CRS 007°	Rwy Idg TDZE Apt Elev	4902 1571 1600
--	------------------------	-----------------------------	---



RNAV (GPS) RWY 1

TITUSVILLE (6G1)


Baro-VNAV NA. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. Night landing: Rwy 1 NA. Use Franklin altimeter setting. When not received, use Port Meade altimeter setting and increase LPV DA to 1899, LNAV/VNAV DA to 1961 and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats visibility 1/8 mile, increase LNAV Cats C/D and Circling Cat C visibility 1/4 mile.

MISSED APPROACH:
Climb to 4500 direct
EVEPE and hold, continue
climb-in-hold to 4500.

FKL AWOS-3PT 118.175	YOUNGSTOWN APP CON * 133.95 322.3	CTAF 122.9 0
---------------------------------------	--	-------------------------------



ELEV 1600	TDZE 1571
MIRL Rwy 1-19 0	



CATEGORY	A	B	C	D
LPV DA	1864-1		293 (300-1)	
LNAV/VNAV DA	1926-1¼		355 (400-1¼)	
LNAV MDA	1980-1	409 (400-1)	1980-1⅛	409 (400-1⅛)
C CIRCLING	2100-1	500 (500-1)	2200-1½ 600 (600-1½)	2280-2¼ 680 (700-2¼)

NE-4, 26 DEC 2024 to 23 JAN 2025

NE-4, 26 DEC 2024 to 23 JAN 2025