

TOP ALTITUDE:
ASSIGNED BY ATC



AUSTI
5000

202°

(26)

MAYNR

MCLAW

FL180
*1300
185°
(34)

(19)
243°
15800

FUNDI

MCLAW

FL180
*1300

265°
(36)

SLIPT

FL180
*1300

275°
(41)

JABOX

FL180
*1300

232°
(15)

MAXIM


FL180
*1300

261°
(41)

CANOA

TAKEOFF MINIMUMS
 Rwy 10: Standard with minimum climb of 500'/NM to 2400.
 Rwy 18: Standard with minimum climb of 500'/NM to 1800.
 Rwy 28: Standard with minimum climb of 500'/NM to 1900.
 Rwy 36: Standard with minimum climb of 500'/NM to 2200.

NOTE: Jet aircraft only.
 NOTE: Accelerate to 250K until leaving
 10000, if unable, advise ATC.



RNAV 1 - DME/DME/IRU or GPS.
 From SLIPT to MAXIM: RNAV 1 - GPS.
 From SLIPT to CANOA: RNAV 1 - GPS.
 RADAR required for non-GPS equipped aircraft.
 RADAR required.

MIAMI DEP CON
 125.5.354.1
 AWOS-3
 118.375
 CTAF
 122.8

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.