WAAS CH 49238 W31A	APP CRS 314°	Rwy ldg 4201 TDZE 1315 Apt Elev 1318

RNAV (GPS) RWY 31
BLAIR EXEC (BTA)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Eppley Airfield altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Eppley Airfield altimeter setting and increase LPV and LNAV/VNAV DA to 1638 and visibility to 1⅛ mile all Cats, increase all MDA 80 feet and LNAV Cat C visibility to 1⅛ mile.

MISSED APPROACH: Climb to 3100 direct BIKPE and hold.

AWOS-3	OMAHA APP CON	UNICOM
120.225	135.875 354.05	123.05 (CTAF) L



ELEV 1318 TDZE 1315



CATEGORY	A	B	C	D
LPV DA	1564-⅞ 250 (300-⅞)			NA
LNAV/VNAV DA	1564-⅞ 250 (300-⅞)			NA
LNAV MDA	1640-1 326 (400-1)			NA
C CIRCLING	1740-1 422 (500-1)	1780-1 462 (500-1)	1780-1½ 462 (500-1½)	NA

REIL Rwy 31 L
MIRL Rwy 13-31 L

NC-2, 26 DEC 2024 to 23 JAN 2025