



WAAS CH 45999 W16A	APP CRS 164°	Rwy Idg TDZE 163 Apt Elev 171
--	------------------------	---

RNAV (GPS) Y RWY 16

BELLINGHAM INTL (BLI)

RNP APCH. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. #RVR 1800 authorized with use of FD or AP or HUD to DA.	MALSR 	MISSED APPROACH: Climb to 700 then climbing right turn to 2000 direct TECUV and hold.
---	--	--

ATIS 134.45	VICTORIA TERMINAL APP CON 132.7 290.8	BELLINGHAM TOWER ★ 124.9 (CTAF) 0 379.3	GND CON 127.4 379.3	UNICOM 122.95
-----------------------	---	---	-------------------------------	-------------------------



4 NM Holding Pattern		SECOG	WUGUT	700	2000	TECUV
			2000	*LNAV only		
		6 NM	4.5 NM	1.1 NM		
CATEGORY	A	B	C	D		
LPV DA #	363/24 200 (200-½)					
LNAV/VNAV DA	491/30 328 (400-¾)					
LNAV MDA	560/24 397 (400-½)		560/35 397 (400-¾)			
CIRCLING	640-1 469 (500-1)		900-2 729 (800-2)		1160-3 989 (1000-3)	