

PHOENIX DEP CON
 124.9 353.8
 ATIS ★
 133.5 270.275
 CINC DEL
 135.05
 GND CON
 128.25 275.8
 GATEWAY TOWER ★
 120.6 289.4

**TOP ALTITUDE:
ASSIGNED BY ATC**

**RNAV 1 - GPS.
RADAR required.**

NOTE: Turbojets and turboprops only.
NOTE: Aircraft requesting FL220 and below must file BLYTHE Transition.
NOTE: Turbojets landing LAX, file WLVRN Transition.
NOTE: Aircraft landing other than LAX and turboprops landing at LAX: Requesting FL240 and above, file HRRBR Transition.
NOTE: Aircraft departing KGEU and KGYR ATC assigned only.

TAKEOFF MINIMUMS
 Rwy 12L/C/R: Standard with a minimum climb of 250'/NM to 3100.
 Rwy 30L/C/R: Standard.

DEPARTURE ROUTE DESCRIPTION
TAKEOFF RUNWAYS 12L/C/R: Climb on heading 124° or as assigned by ATC, thence. . . .
TAKEOFF RUNWAYS 30L/C/R: Climb on heading 304° or as assigned by ATC, thence. . . .
 . . . for RADAR vectors to KEENS, then on track 259° to IZZO, then on (transition).
 Maintain ATC assigned altitude, expect filed altitude 3 minutes after departure.

BLYTHE TRANSITION (IZZZO8.BLH)
HRRBR TRANSITION (IZZZO8.HRRBR)
WLVRN TRANSITION (IZZZO8.WLVRN)

NOTES: Chart not to scale.