

WAAS

CH **81806**

W06B

APP CRS

058°

Rwy Idg

8029

TDZE

777

Apt Elev

799

RNAV (GPS) Y RWY 6R

CLEVELAND-HOPKINS INTL (CLE)

RNP APCH.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 46°C (114°F). Circling Rwy 10 NA at night. For inop ALS, increase LNAV Cats C/D visibility to 1½ SM.

MALSR

As

MISSED APPROACH: Climb to 3000 direct MOMBE and on track 099° to NEILL and hold.

D-ATIS	CLEVELAND APP CON	CLEVELAND TOWER	GND CON	CLNC DEL	CPDLC
ARR 127.85 DEP 132.375	126.55 346.325	124.5 273.45	121.7 273.45	125.05 273.45	

EC-2, 23 JAN 2025 to 20 FEB 2025

ELEV	799	TDZE	777
------	-----	------	-----

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

DOORZ

POAST

DILYN

3000

MOMBE

tr 099°

NEILL

*LNAV only.

GP 3.10°

TCH 58

2900

058°

2500

2000

2000

*1.4 NM to RWY06R

RWY06R

1.4 NM

1.6 NM

2.2 NM

1.4 NM

CATEGORY	A	B	C	D
LPV DA	977/18 200 (200-½)			
LNAV/VNAV DA	1227/45 450 (500-¾)			
LNAV MDA	1260/24 483 (500-½)	1260/50 483 (500-1)		
CIRCLING	1420-1 621 (700-1)	1420-1¾ 621 (700-1¾)	1420-2 621 (700-2)	

REIL Rwy 10

TDZ/CL Rwy 6L, 6R, 24L, and 24R

HIRL Rwy 6L-24R, 6R-24L and 10-28

CLEVELAND, OHIO

Amtd 3 24MAY18

41°25'N-81°51'W

CLEVELAND-HOPKINS INTL (CLE)

RNAV (GPS) Y RWY 6R