

LOC/DME I-DTW 110.7 Chan 44	APP CRS 036°	Rwy Idg TDZE Apt Elev	11494 640 645
---	------------------------	-----------------------------	--

ILS or LOC RWY 4R
DETROIT METRO WAYNE COUNTY (DTW)

RNAV 1-GPS.
CLEVR, CAATZ and ELDNN: RNAV 1-DME/DME/IRU or GPS required.
Aircraft not DME/DME/IRU or GPS equipped - RADAR required for procedure entry.
DME or RADAR required.

Simultaneous approach authorized. For inop ALS, increase S-LOC 4R
Cat C/D visibility to RVR 6000.

ALSF-2


MISSED APPROACH: Climb
to 4000 on DXO VOR/DME
R-035 to LUPAY/DXO VOR/
DME/15.6 DME and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 128.125 317.725	121.8 GND CON 132.725 (NW) (SW)	119.45 (NE) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	---------------------------------------	--	--	---------------------------	-------


ALTERNATE MISSED
APCH FIX

LOCALIZER **110.7**
I-DTW
Chan **44**

MISSED
APCH
FIX



BAANG I-DTW RADAR	JULEP I-DTW RADAR	CULOP I-DTW RADAR	HIMEX I-DTW RADAR	EVABE I-DTW RADAR	JELLY I-DTW RADAR	ETALE I-DTW RADAR	LUPAY DXO
25	21.9	18.8	15.6	12.5	9.3	6.2	15.6
8000	7000	6000	5000	4000	3000	2000	
GS 3.00° TCH 52	3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.2 NM	3 NM
CATEGORY	A	B	C	D			
S-ILS 4R	840/18 200 (200-1/2)						
S-LOC 4R	1040/24	400 (400-1/2)	1040/35	400 (400-1/2)			
CIRCLING	1180-1	535 (600-1)	1180-1 1/2 535 (600-1 1/2)	1240-2 595 (600-2)			



EC-1, 23 JAN 2025 to 20 FEB 2025

EC-1, 23 JAN 2025 to 20 FEB 2025