

WAAS CH 48820 W35A	APP CRS 352°	Rwy Idg TDZE Apt Elev	6002 917 930
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35R
SOUTH TEXAS RGNL AT HONDO (HDO)

RNP APCH.

▼ Baro-VNAV NA when using Castrovilla altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). Visibility reduction by helicopters NA. When local altimeter setting not received, use Castrovilla altimeter setting and increase all DA 62 feet and all MDA 80 feet, increase LNAV/VNAV all Cats, and LNAV and Circling Cats C and D visibility ¼ mile. Circling Rwy 8, 13, 17R, 26, 31, 35L NA at night.

MISSED APPROACH:
Climb to 3700 direct
JENDE and hold.

ASOS 119.675	HOUSTON CENTER 134.95 269.4	UNICOM 122.725 (CTAF)
------------------------	---------------------------------------	---------------------------------

MISSED APCH FIX

¹⁴⁴⁸Δ

Procedure NA for arrival on SAT
VORTAC airway radials 175 CW 190.

SAN ANTONIO
SAT

Diagram of a beam with a 4000 lb point load at 220 degrees, 43.2 ft from the left support.

Process VORT

1220

BS1

W1

L1

D1

W2

L2

D2

BS2

Q

D3

ELEV 930

TDZE 917

MIRL Rwy 17L-35R

Orig-B 15JUL21

29°22'N-99°11'W

SOUTH TEXAS RGNL AT HONDO (HDO)

RNAV (GPS) RWY 35R

SC-3, 23 JAN 2025 to 20 FEB 2025