

WAAS

CH **53528**

W18A

APP CRS

180°

Rwy Idg

5199

TDZE

430

Apt Elev

430

RNAV (GPS) RWY 18

LAWRENCEVILLE-VINCENNES INTL (L WV)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 41°C (105°F).
DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Mount Carmel altimeter setting. When local altimeter setting not received, use Mount Carmel altimeter setting: increase LPV DA 656 feet; increase LNAV/VNAV DA to 902 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV visibility Cat C/D ¼ SM; and Circling visibility Cat D ¼ SM. Circling to Rwy 36 NA at night.

MISSED APPROACH:

Climb to 2600 direct VOCUT and hold.

ASOS 118.0	EVANSVILLE APP CON ★ 125.6 343.7	UNICOM 122.8 (CTAF) ①
----------------------	--	---------------------------------

The main chart displays the RNAV (GPS) RWY 18 approach. Key features include:

- Initial Approach:** 30 NM to ZAKEB, 090° heading, 2600 ft NoPT (10) MDA.
- Intermediate Approach:** 30 NM to JEBDU, 180° heading, 2600 ft NoPT (10) MDA.
- Final Approach:** 30 NM to PICNO, 271° heading, 2600 ft NoPT (10) MDA.
- Altitudes:** 1200 ft, 2100 ft, 2600 ft, 453 ft, 569 ft, 649 ft.
- Navigation Aids:** (IAF) ZAKEB, (IF/IAF) JEBDU, (FAF) LUKMY, KEBNE, RWY 18.
- Obstacles:** 1028 ft, 792 ft.
- MISSED APCH FIX VOCUT:** 360° heading, 4 NM distance.

4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).		2600	VOCUT	
JEBDU		LUKMY		*LNAV only.		
2600		2100		KEBNE 1.9 NM to RWY 18		
GP 3.00° TCH 45		*1060		RWY 18		
6.8 NM		3.2 NM		1.9 NM		
CATEGORY	A	B	C	D		
LPV DA	630-¾		200 (200-¾)			
LNAV/VNAV DA	876-1½		446 (500-1½)			
LNAV MDA	940-1	510 (600-1)	940-1¾	510 (600-1¾)		
CIRCLING	940-1	510 (600-1)	940-1½	510 (600-1½)	1160-2¼	730 (800-2¼)

ELEV 430

TDZE 430

180° to RWY 18

5198 X 100

81

27

5199 X 100

36

Ultralight Area

REIL Rwy 9, 27, 18 and 36 ①

MIRL Rwy 9-27 and 18-36 ①

LAWRENCEVILLE, ILLINOIS

Amtd 1C 19MAY22

38°46'N - 87°36'W

LAWRENCEVILLE-VINCENNES INTL (L WV)

RNAV (GPS) RWY 18