

OAKLAND CENTER
127.8 353.5
ATIS
124.05
CLNC DEL
127.85
GND CON
121.7
NAPA TOWER★
118.7 (CTAF) 257.8

TOP ALTITUDE:
ASSIGNED BY ATC

TAKEOFF MINIMUMS
Rwy 1L: Standard with minimum climb of 420' per NM to 2900.
Rwy 1R: Standard with minimum climb of 460' per NM to 3000.
Rwy 6: Standard with minimum climb of 430' per NM to 1600.
Rwy 19L: Standard with minimum climb of 320' per NM to 1500.
Rwy 19R: Standard with minimum climb of 330' per NM to 1600.
Rwy 24: Standard with minimum climb of 255' per NM to 1300.

RED BLUFF
115.7 RBL
Chan 104

WILLIAMS
114.4 ILA
Chan 91

MENDOCINO
112.3 ENI
Chan 70

SACRAMENTO
115.2 SAC
Chan 99

SCAGGS ISLAND
112.1 SGD
Chan 58

LINDEN
114.8 LIN
Chan 95

POINT REYES
113.7 PYE
Chan 84

CONCORD
117.0 CCR
Chan 117

SAUSALITO
116.2 SAU
Chan 109

OAKLAND
116.8 OAK
Chan 115

(CONTINUED ON FOLLOWING PAGE)

NOTE: RADAR required.
NOTE: Chart not to scale.

SW-2, 23 JAN 2025 to 20 FEB 2025

SW-2, 23 JAN 2025 to 20 FEB 2025