


WAAS CH 70306 W11A	APP CRS 110°	Rwy Idg TDZE 76 Apt Elev 76	7200
--	------------------------	---	-------------

RNAV (GPS) RWY 11
PORTLAND INTL JETPORT (PWM)

RNP APCH - GPS.			ALSF-2	MISSED APPROACH: Climb to 3000 direct SAPPE and hold, continue climb-in-hold to 3000.	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.					
ATIS 119.05	PORTLAND APP CON ★ 119.75 269.35	PORTLAND TOWER ★ 120.9 0 (CTAF) 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95



4 NM Holding Pattern		BUXTO	3000	SAPPE
		MAINA		
2300 ← 290°		1800	FINUS 1.8 NM to RW11	* LNAV only
GP 3.00° TCH 51		1800	RW11	
		4 NM	3.5 NM	1.8 NM
CATEGORY	A	B	C	D
LPV DA		276/18	200 (200-½)	
LNAV/VNAV DA		456/40	380 (400-¾)	
LNAV MDA	520/24	444 (500-½)	520/45	444 (500-¾)
CIRCLING	620-1 544 (600-1)	640-1 564 (600-1)	740-1¾ 664 (700-1¾)	860-2½ 784 (800-2½)

