

HI-ILS or LOC RWY 10

LOC I-SAV 111.35 Chan 50 (Y)	APCH CRS 097°	Rwy Idg TDZE 30 Arpt Elev 50	AL-380 [USAF]	SAVANNAH/HILTON HEAD INTL (KSAV)
--	-------------------------	--	---------------	----------------------------------

DME required

Procedure NA when Control Tower closed.
 * When ALS inop, increase vis to RVR 40
 ** When ALS inop, increase vis to 1½ miles.

MALS R 5 MISSED APPROACH: Climb to 800, then climbing left turn to 4000 via heading 330° and SAV VORTAC R-001 to TILLS/SAV 20 DME and hold.

ATIS ★ 123.75	APP CON 125.3 353.775	TOWER ★ 125.975 (CTAF) 257.8	GND CON 121.9 348.6	CLNC DEL 119.55 291.775
-------------------------	---------------------------------	--	-------------------------------	-----------------------------------

Use I-SAV DME when on the localizer course.
VGSI and ILS glidepath not coincident.
VGSI angle 3.00/TCH 69.

CATEGORY	C	D	E
S-ILS 10 *	230/18	200	(200-½)
S-LOC 10 **	500/50	470	(500-1)
CIRCLING	740-2 690 (700-2)	740-2¼ 690 (700-2¼)	900-3 850 (900-3)

REIL Rwys 19, 28
HIRL all Rwy
TDZL/CL Rwy 10