

WAAS CH 58006 W12A	APP CRS 121°	Rwy Idg 7504 TDZE 402 Apt Elev 410
--	------------------------	---


RNAV (GPS) Y RWY 12

TRI-CITIES (PSC)


⚠ Baro-VNAV NA when using Hermiston altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Hermiston altimeter setting. When local altimeter setting not received, use Hermiston altimeter setting: increase all DA 95 feet and all MDA 100 feet. Increase LPV all Cats visibilities ½ mile; LNAV/VNAV all Cats visibilities ⅓ mile; increase LNAV and Circling Cats C and D visibility ¼ mile.

MISSED APPROACH:
Climb to 900 then climbing left turn to 3200 direct CITYS and hold.

ATIS 125.65	SPOKANE APP CON ★ 128.75 377.2	TRI-CITIES TOWER ★ 135.3 (CTAF) 0 323.3	GND CON 121.8	CLNC DEL 120.0	UNICOM 122.95
-----------------------	--	---	-------------------------	--------------------------	-------------------------



ELEV 410	D	TDZE 402
----------	----------	----------



				900				3200				CITY					
				↑				↙				△					
								*LNAV only									
								*1.2 NM to RW12				RW12					
CATEGORY		A		B		C		D									
LPV DA		602-¾ 200 (200-¾)															
LNAV/VNAV DA		755-1½ 353 (400-1½)															
LNAV MDA		840-1 438 (500-1)						840-1¾ 438 (500-1¾)									
CIRCLING		880-1 470 (500-1)				940-1 530 (600-1)				1040-1¾ 630 (700-1¾)				1100-2¼ 690 (700-2¼)			