EDWARDS, CALIFORNIA

RNAV (GPS) RWY 23L

EDWARDS AFB (KEDW)

APCH CRS	Rwy ldg	15,024
226°	TDZE	2286
	Arpt Elev	2311

- (USAF)

* Circling not authorized NW of Rwy 5L-23R.

MISSED APPROACH: Climb to 5700 direct LDFRD, continue climb-in-hold to 5700.

ATIS★	JOSHUA APP CON/DEP CON	TOWER★	GND CON
127.425 269.9	133.65 348.7	120.7 (CTAF) 318.1 (CTAF)	121.8 225.4

5010

For uncompensated Baro-VNAV systems, Procedure NA below -19° C (-2°F) or above 54°C (130°F).

DME/DME RNP-0.3 NA

(IAF) XPLNE 8500

3310

4584

(IAF) SONIQ 8500

6100 162° (10.8)

6100 226° (12.4)

(IF/IAF) HAARS 6100

4500 226° (6.5)

6100 293° (10.9)

(FAF) KIIRK

3404

(IAF) STLTH 8500

RW23L

2674

2342

2379

226°

LDFRD

046°

5 NM

3424

HOLD 8500 4500

MSA RW23L 25 NM

7700

EMERG SAFE ALT 100 NM 16,500

5700

LDFRD

HAARS

6100

226°

KIIRK

RW23L

1 NM to RW23L

4500

GP 3.00°

TCH 51

6.7 NM

ELEV 2311

TDZE 2286

TWR

BCN 2463

226°

23R

23L

12,000 x 200

15,024 x 300

2342

5L

5R

8000 x 50

5

CATEGORY	A	B	C	D	E
LNAV/VNAV DA	2620-1		334	(400-1)	
LNAV MDA	2660-1		374	(400-1)	
C CIRCLING*	2880-1 569 (600-1)		2880-1½ 569 (600-1½)	2880-2 569 (600-2)	

HIRL Rwy 5R-23L
REIL Rwy 23L

SW-3, 23 JAN 2025 to 20 FEB 2025

SW-3, 23 JAN 2025 to 20 FEB 2025