


LOC I-HLG	APP CRS	Rwy Idg
109.7	033°	5002
		TDZE
		1172
		Apt Elev
		1194

ILS or LOC RWY 3

WHEELING OHIO COUNTY (HLG)

DME or RADAR required.			MALSF	MISSED APPROACH: Climb to 1700 then climbing right turn to 3100 direct HLG VOR/DME and hold. Continue climb-in-hold to 3100.	
Autopilot coupled approach NA below 1401. Inop table does not apply to S-ILS all Cats and S-LOC Cats A/B.					
ASOS	PITTSBURGH APP CON	WHEELING TOWER *	GND CON	CLNC DEL	UNICOM
127.375	125.275 285.575	118.1(CTAF) 257.8	121.75	125.275 (when twr closed)	122.95



Remain within 10 NM		CESKA HLG 10.9 RADAR	1700	3100	HLG
3100		213°	↑	↷	☐
GS 3.00° TCH 60		033°	*LOC only.		
2600		2600	*1800		
		2.5 NM	0.5 NM	1.3 NM	
CATEGORY	A	B	C	D	
S-ILS 3		1372/50	200 (200-1)		
S-LOC 3	1800/50	628 (700-1)	1800-1½	628 (700-1½)	
CIRCLING	1800-1	606 (700-1)	1920-2 726 (800-2)	1920-2¼ 726 (800-2¼)	
YIZQI FIX MINIMUMS					
S-LOC 3	1640/50	468 (500-1)	1640/60	468 (500-1¼)	
CIRCLING	1720-1 526 (600-1)	1740-1 546 (600-1)	1920-2 726 (800-2)	1920-2¼ 726 (800-2¼)	

