

Rwy 2: Standard with minimum climb of 300' per NM to 2100.

Rwy 14: Standard with minimum climb of 285' per NM to 2500.

Rwy 20: Standard with minimum climb of 265' per NM to 2200.

Rwy 32: Standard with minimum climb of 375' per NM to 2200.

NOTE: Chart not to scale.

## 77

SW-2, 23 JAN 2025

ō

20 FEB 2025

## DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climbing left turn on heading 305° (or as assigned between 200° CW to 305° from departure end of runway), thence . . . .

TAKEOFF RUNWAY 14: Climb on heading 144° (or as assigned between 110° CW to 315° from departure end of runway), thence . . . .

TAKEOFF RUNWAY 20: Climb on heading 196° (or as assigned between 100° CW to 250° from departure end of runway), thence . . . .

TAKEOFF RUNWAY 32: Climbing left turn on heading 315° (or as assigned between 145° CW to 315° from departure end of runway), thence . . . .

. . . . expect RADAR vectors to join assigned route. Maintain ATC assigned altitude; expect filed altitude/flight level ten minutes after departure.

<u>LOST COMMUNICATIONS</u>: If not in contact with Oakland Center after reaching 4000, proceed direct to the PYE VOR/DME. Thence via assigned route.