

APP CRS	Rwy Idg	5320
046°	TDZE	16
	Apt Elev	17

RNAV (RNP) Z RWY 5

SOUTHWEST OREGON RGNL (OTH)


RNP AR APCH. RF required.

For inop ALS, increase *RNP 0.11 all Cats visibility to 1 SM, #RNP 0.30 all Cats visibility to 1½ SM, and RNP 0.30 all Cats visibility to 1½ SM. For uncompensated Baro-VNAV systems, procedure NA below -2°C or above 54°C.

MALSR

MISSED APPROACH: Climb to 3300 on track 046° to EJLEL, left turn to ERQAS, and on track 138° to OTH VOR/DME and hold.
* Missed approach requires minimum climb of 400 feet per NM to 1200.
Missed approach requires minimum climb of 255 feet per NM to 2400.

AWOS-3PT 135.075	SEATTLE CENTER 127.55 254.35	NORTH BEND TOWER* 118.45 (CTAF) 0	GND CON 127.1
---------------------	---------------------------------	--------------------------------------	------------------



See planview for multiple IF locations.

FOGIX

1900

046°

GP 3.00°

TCH 51

2.1 NM

3.9 NM

3300

EJLEL

ERQAS

tr 138°

OTH

RW05

CATEGORY

A

B

C

D

RNP 0.11 DA*

394-5⁄8

378 (400-5⁄8)

RNP 0.30 DA#

477-1½

461 (500-1½)

RNP 0.30 DA

569-1¾

553 (600-1¾)

AUTHORIZATION REQUIRED

ELEV 17

TDZE 16

HIRL Rwy 5-23

MIRL Rwy 13-31

REIL Rwys 13, 23 and 31