


WAAS CH 69415 W01A	APP CRS 013°	Rwy Idg TDZE Apt Elev	8000 63 75
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) RWY 1R

BRUNSWICK EXEC (BXM)

▼ ▲	Baro-VNAV NA when using Portland altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA when using Portland altimeter setting. When local altimeter setting not received, use Portland altimeter setting and increase LPV DA to 314, LNAV/VNAV DA to 461 and all LNAV/VNAV visibilities ¼ SM; increase all MDA 60 feet and LNAV Cat C/D visibilities ¼ SM and Circling Cat C/D visibilities ¼ SM. For inop ALS when using Portland altimeter setting, increase LNAV Cat C/D visibility to 1 ½ SM.			MALSR MISSED APPROACH: Climb to 2500 direct WODGI and hold.
	AWOS-3PT 134.875	PORTLAND APP CON ★ (112°-292°) 119.75 269.35 (293°-111°) 120.4 299.2		



ELEV	75	TDZE	63
------	-----------	------	-----------



2500

WODGI

↑

2500

✦

WODGI

* LNAV only.

RW01R

*1.2 NM to RW01R

1.2 NM

1.3 NM

2.5 NM

6.7 NM

ZETGU

2.5 NM to RW01R

CARMR

1700

BAILI

4 NM Holding Pattern

193°

← 013°

2000

013°

1700

GP 3.00°

TCH 50

*900

CATEGORY	A	B	C	D
LPV DA		263-½	200 (200-½)	
LNAV/VNAV DA		410-⅝	347 (400-⅝)	
LNAV MDA	500-½	437 (500-½)	500-¾	437 (500-¾)
CIRCLING	560-1	485 (500-1)	840-2¼ 765 (800-2¼)	840-2½ 765 (800-2½)