


APP CRS	Rwy Idg	10000
036°	TDZE	645
	Apt Elev	645

RNAV (RNP) X RWY 4L

DETROIT METRO WAYNE COUNTY (DTW)

RNP AR APCH.			ALS-F2		MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct DOHNT and hold.	
Simultaneous approach authorized. For uncompensated Baro-VNAV systems, procedure NA below -19°C or above 54°C. For inop ALS, increase RNP 0.30 DA all Cnts visibility to RVR 6000.						
D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 135.0 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)		CLNC DEL 120.65	CPDLC



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 71).				
ASLLI NATIY REGGE PAYED RWY04L				
3000 036° 3000 3000 2000 2000				
GP 3.00° TCH 55				
4.2 NM 3.1 NM 3.1 NM 4.1 NM				
CATEGORY	A	B	C	D
RNP 0.15 DA		970/26	325 (400-½)	
RNP 0.30 DA		1058/40	413 (500-¾)	
AUTHORIZATION REQUIRED				

