

WAAS CH 40402 W17A	APP CRS 172°	Rwy Idg TDZE Apt Elev	11759 234 234
--	------------------------	-----------------------------	--

RNAV (GPS) RWY 17

PLATTSBURGH INTL (PBG)

RNP APCH - GPS.


▼

▲


Baro-VNAV and VDP NA when using BTV altimeter setting. When local altimeter not received, use BTV altimeter setting and increase LPV DA to 615 feet and all visibilities $\frac{1}{8}$ SM. Increase LNAV/VNAV DA to 770 feet and all visibilities $\frac{1}{8}$ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D/E $\frac{1}{4}$ SM, and Circling visibility Cat C/D $\frac{1}{4}$ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MISSED APPROACH:
Climb to 3000 direct CAPNU and hold.

ASOS 132.225	BURLINGTON APP CON ★ 121.1 278.8	CLNC DEL 121.85	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------	---------------------------------



ELEV	234	D	TDZE	234
------	------------	----------	------	------------



4 NM Holding Pattern		VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 40).		3000	CAPNU
OTGOE		JUKBA		NUPIY 2.4 NM to RW17	
6000 3500		2500		1.5 NM to RW17	
GP 3.00° TCH 54		2500		RW17	
6 NM		4.5 NM		1 NM	
CATEGORY	A	B	C	D	E
LPV DA	561-3/4		327 (400-3/4)		
LNAV/VNAV DA	716-13/8		482 (500-13/8)		
LNAV MDA	740-1	506 (600-1)	740-13/8	506 (600-13/8)	
CIRCLING	740-1	506 (600-1)	800-11/2 566 (600-11/2)	960-21/4 726 (800-21/4)	1100-3 866 (900-3)