


APP CRS	Rwy Idg	9500
011°	TDZE	1017
	Apt Elev	1027

RNAV (RNP) Z RWY 1R
KANSAS CITY INTL (MCI)

RNP AR APCH - GPS.	ALSF-2 	MISSED APPROACH: Climb to 1500 then climbing right turn to 4000 direct ANX VORTAC and hold.
Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -19°C or above 54°C. Simultaneous approach authorized, except for arrivals at FIDVU, BRSKT, BAUNR and COOKD. For inop ALS, increase RNP 0.30 all Cats visibility to RVR 4500.		

D-ATIS 128.375	KANSAS CITY APP CON 120.95 318.1	INTERNATIONAL TOWER 128.2 254.25	GND CON 121.8	CLNC DEL 135.7	CPDLC
-------------------	-------------------------------------	-------------------------------------	------------------	-------------------	-------



RIBBS		VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 74).		1500	4000	ANX
2900						
2900		011°		RW01R		
GP 3.00° TCH 59°		See planview for multiple IF locations.				
		5.7 NM				
CATEGORY	A	B	C	D		
RNP 0.30 DA	1280/24		263 (300-½)			
AUTHORIZATION REQUIRED						

