

WAAS
CH **48912**
W32A

APP CRS
319°

Rwy Idg
TDZE **53**
Apt Elev **53**

RNAV (GPS) RWY 32

SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 49°C. When local altimeter setting not received use Georgetown altimeter setting: increase LPV DA to 305 feet; increase LNAV/VNAV DA to 510; increase all MDA 60 feet and LNAV Cat C and Circling Cat D visibility ¼ SM. For inoperative MALSRR, increase LNAV Cat D visibility to 1¼ SM. VDP and Baro-VNAV NA when using Georgetown altimeter setting.

MALSRR

MISSED APPROACH:
Climb to 2100 direct HYDRS and hold.

ASOS
118.325

PATUXENT APP CON★
127.95 314.0

SALISBURY TOWER★
119.425 (CTAF) 0

GND CON
123.775

CLNC DEL
123.775

CLNC DEL
118.55
(when twr closed)

UNICOM
122.95

ELEV 53

D

TDZE 53

TWR 128

REIL Rwy 5, 14 and 23

MIRL Rwy 5-23

HIRL Rwy 14-32

2100 HYDRS

*LNAV only

COLBE

FRYER

4 NM Holding Pattern

2000

139°

319°

2000

GP 3.00°

TCH 54

1 NM

1 NM

3.9 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA	253-½		200 (200-½)	
LNAV/VNAV DA	458-1		405 (500-1)	
LNAV MDA	420-½ 367 (400-½)		420-1 367 (400-1)	
CIRCLING	480-1 427 (500-1)	520-1 467 (500-1)	560-1½ 507 (600-1½)	700-2 647 (700-2)

SALISBURY, MARYLAND

AmDt 2A 25MAR21

SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

38°20'N-75°31'W

RNAV (GPS) RWY 32