

WAAS CH 62820 W05A	APP CRS 049°	Rwy Idg TDZE Apt Elev	5000 48 53
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 5


SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

RNP APCH.

▼ Baro-VNAV NA when using Georgetown altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 49°C. Visibility reduction by helicopters NA. When local altimeter setting not received use Georgetown altimeter setting: increase LPV DA to 394 feet and increase all Cats visibility ¼ SM; increase LNAV/VNAV DA to 512 feet and all Cats visibility ¼ SM; increase all MDA 60 feet and LNAV Cat C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 direct OKKOE and hold.

ASOS 118.325	PATUXENT APP CON ★ 127.95 314.0	SALISBURY TOWER ★ 119.425 (CTAF) 0	GND CON 123.775	CLNC DEL 123.775	CLNC DEL 118.55 (when twr closed)	UNICOM 122.95
------------------------	---	---	---------------------------	----------------------------	--	-------------------------



4 NM Holding Pattern FEYKO		*LNAV only. 2000 OKKOE	
2000 ← 229° / 049° →		GP 3.00° / TCH 39	
2000		2000	
8.1 NM		3.4 NM	
2.5 NM		RW05	
*880		ZAGID 2.5 NM to RW05	
CATEGORY	A	B	C
LPV DA	342-1		294 (300-1)
LNAV/VNAV DA	460-1½		412 (500-1½)
LNAV MDA	440-1		392 (400-1)
CIRCLING	480-1 427 (500-1)	520-1 467 (500-1)	560-1½ 507 (600-1½)

