

WAAS
CH **77909**
W27A

APP CRS
269°

Rwy Idg
TDZE
387
Apt Elev
387

RNAV (GPS) RWY 27

HENDERSON CITY-COUNTY (EHR)

▼

⚠

Baro-VNAV NA when using Evansville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 27 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Evansville altimeter setting and increase all DA 41 feet and all MDA 60 feet and LPV all Cats, LNAV/VNAV all Cats and LNAV Cats C/D visibilities ¼ mile.

MISSED APPROACH: Climb to 2500 direct BIKME and hold.

AWOS-3PT 118.85	EVANSVILLE APP CON ★ 124.025 257.8	UNICOM 122.8 (CTAF) 0
---------------------------	--	--

The main chart displays the RNAV (GPS) approach for RWY 27. Key features include:

- Navigation Aids:** DARGE (30 NM to DARGE), GOTVE (1.7 NM to RW27), SIZBY (FAF), ENOKE (IAF), and ONZIG (IF/IAF).
- Altitudes:** 2500, 2200, 269°, 270°, 2500 NoPT, 2500 NoPT, 2600, 2500.
- Distances:** 30 NM to DARGE, 1.7 NM to RW27, 4 NM, 30 NM to ENOKE, 15 NM to ONZIG (NoPT), 30 NM to ONZIG (NoPT).
- Angles:** 180°, 090°, 270°, 360°, 180°.
- Missed Approach:** MISSED APCH FIX BIKME, 089°, 269°, 4 NM.

ELEV 387

TDZE 387

2500

BIKME

*LNAV only

GOTVE 1.7 NM to RW27

RW27

269°

270°

2200

ONZIG

4 NM Holding Pattern

090°

270°

2500

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	733-1¼ 346 (400-1¼)			
LNAV/VNAV DA	827-1½ 440 (500-1½)			
LNAV MDA	840-1	453 (500-1)	840-1¾ 453 (500-1¾)	840-1½ 453 (500-1½)

HENDERSON, KENTUCKY

Amdt 1A 18JUL19

37°48'N-87°41'W

HENDERSON CITY-COUNTY (EHR)

RNAV (GPS) RWY 27