

WAAS CH 42719 W06A	APP CRS 065°	Rwy Idg 3523 TDZE 301 Apt Elev 302
--	------------------------	---

RNAV (GPS) RWY 6
WINGS FLD (LOM)


RNP APCH

T Baro-VNAV NA when using Pottstown altimeter setting. For uncompensated
A Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). When local altimeter setting not received, use Pottstown altimeter setting and increase all DA 35 feet and all MDA 40 feet; increase LPV Cats A/B visibility ¼ mile. Rwy 6 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2000
direct HOMWE and hold.

AWOS-3 118.925	PHILADELPHIA APP CON 126.85 263.125	CLNC DEL 118.55	UNICOM 123.0 (CTAF) 0
--------------------------	---	---------------------------	---------------------------------

Procedure NA for arrival
at PTW VORTAC on
V403-405 northeast bound



4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 40).

CATEGORY	A	B	C	D
LPV DA	614-1	313 (400-1)		NA
LNAV/VNAV DA	788-1 ³ / ₄	487 (500-1 ³ / ₄)		NA
LNAV MDA	720-1	419 (500-1)		NA
CIRCLING	780-1	478 (500-1)		NA

