

WAAS CH 42532 W28A	APP CRS 278°	Rwy Idg TDZE Apt Elev	5501 621 621
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28

MANISTEE COUNTY/BLACKER (MBL)

RNP APCH - GPS.


Circling to Rwy 1, 19 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

MALSRL

MISSED APPROACH:

Climb to 2500 direct GOSDE and hold.

AWOS-3PT 118.825	MINNEAPOLIS CENTER 120.85 322.35	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



ELEV 621

TDZE 621

2500

GOSDE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).

4 NM Holding Pattern

CATEGORY	A	B	C	D
LPV DA	821-1/2 200 (200-1/2)			
LNAV/VNAV DA	984-5/8 363 (400-5/8)			
LNAV MDA	1060-1/2 439 (500-1/2)	1060-3/4 439 (500-3/4)		
CIRCLING	1160-1 539 (600-1)	1220-1 599 (600-1)	1400-2 1/4 779 (800-2 1/4)	1500-2 3/4 879 (900-2 3/4)

HIRL Rwy 10-28

MIRL Rwy 1-19

REIL Rwy 10

EC-1, 20 MAR 2025 to 17 APR 2025

EC-1, 20 MAR 2025 to 17 APR 2025