



LOC I-CKV 111.7	APP CRS 347°	Rwy Idg TDZE Apt Elev	5999 550 550
---------------------------	------------------------	-----------------------------	---

LOC RWY 35

OUTLAW FLD (CKV)

ADF required. RADAR required.	MALS	MISSED APPROACH: Climb to 1800 then climbing right turn to 2200 direct CKV VOR/DME and hold.
⚠ Circling NA W of Rwy 17-35. Circling Rwy 5, 17, 23 NA at night. Rwy 35 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Campbell AAF (Fort Campbell) altimeter setting. * DME from CKV VOR/DME.		

ASOS 134.575	CAMPBELL APP CON 134.35 307.025	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



1800	2200	CKV	CK LOM CKV 5.8	VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 54). Remain within 10 NM
167°	347°	2700	1080	2300
2.5 NM	2.8 NM			
CATEGORY	A	B	C	D
S-LOC 35	1080-¾ 530 (600-¾)		1080-1¼ 530 (600-1¼)	
CIRCLING	1080-1 530 (600-1)		1080-1½ 530 (600-1½)	1200-2 650 (700-2)
YORUK FIX MINIMUMS * (DME REQUIRED)				
S-LOC 35	880-¾ 330 (400-¾)			
CIRCLING	1000-1 450 (500-1)	1020-1 470 (500-1)	1020-1½ 470 (500-1½)	1200-2 650 (700-2)