

VOR/DME CKV
110.6
Chan **43**

APP CRS
357°

Rwy Idg
TDZE **550**
Apt Elev **550**

5999
550
550

VOR RWY 35
OUTLAW FLD (CKV)

RADAR required for procedure entry.


T

Circling NA W of Rwy 17-35. Circling Rwy 5, 17, 23 NA at night. Rwy 35 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Campbell AAF (Fort Campbell) altimeter setting.

MALS
A4

MISSED APPROACH:
Climb to 1500 then climbing right turn to 2200 direct CKV VOR/DME and hold.

ASOS 134.575	CAMPBELL APP CON 134.35 307.025	UNICOM 122.8 (CTAF)
------------------------	---	-------------------------------



598 4004 X 1000 5999 X 100 35 357°

REIL Rwy 17 MRL Rwy 17-35

1500 2200 CKV

CKV VOR/DME

Remain within 10 NM

177 2300 357 2.1 1.6 NM

CATEGORY	A	B	C	D
S-35	1120-1 570 (600-1)		1120-1½ 570 (600-1½)	1120-1¾ 570 (600-1¾)
CIRCLING	1120-1 570 (600-1)		1120-1½ 570 (600-1½)	1200-2 650 (700-2)

SE-1, 20 MAR 2025 to 17 APR 2025

SE-1, 20 MAR 2025 to 17 APR 2025