

LOC/DME I-JFX	APP CRS	Rwy Idg	4800
108.9	273°	TDZE	481
Chan 26		Apt Elev	483

ILS or LOC RWY 27

WALKER COUNTY/BEVILL FLD (JFX)


DME required.

NA

Rwy 27 helicopter visibility reduction below $\frac{3}{4}$ SM NA. VDP NA when using Birmingham altimeter setting. When local altimeter setting not received, use Birmingham altimeter setting: increase DA to 892 feet and S-ILS all Cats visibilities $\frac{1}{4}$ SM; increase all MDAs 120 feet and S-LOC Cats C and D and Circling Cats C and D visibility $\frac{1}{4}$ SM.

MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 on VUZ VORTAC R-298 to NEGEE/16 DME and hold.

AWOS-3PT 119.225	BIRMINGHAM APP CON 127.675 338.2	GCO 121.725	UNICOM 123.075 (CTAF) 0
----------------------------	--	-----------------------	-----------------------------------



ELEV 483	D	TDZE 481
----------	----------	----------

MIRL Rwy 9-27 0
REIL Rwy 9 and 27 0

1500	3000	VUZ R-298	NEGEE	MAYLE I-JFX (6.1)	SIPSY I-JFX (14.8)	One Minute Holding Pattern
*LOC only						
GS 3.00° TCH 44						
CATEGORY	A		B		C	
S-ILS 27	788- $\frac{7}{8}$		307 (400- $\frac{7}{8}$)			
S-LOC 27	1040-1 559 (600-1)		1040-1 $\frac{5}{8}$ 559 (600-1 $\frac{5}{8}$)			
C CIRCLING	1040-1 557 (600-1)		1080-1 597 (600-1)		1160-2 677 (700-2)	
					1360-2 $\frac{3}{4}$ 877 (900-2 $\frac{3}{4}$)	