

WAAS CH 82206 W15A	APP CRS 147°	Rwy Idg 11820 TDZE 504 Apt Elev 504
--	------------------------	--

RNAV (GPS) RWY 15


GRIFFISS INTL (RME)

RNP APCH-GPS.


▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 48°C.
▲ When local altimeter setting not received, use Syracuse altimeter setting and increase LPV DA to 804 feet, LNAV/VNAV DA to 1152 feet and all MDA 100 feet. Increase LNAV/VNAV all Cats, LNAV Cats C and D and Circling Cats B and C visibility ¼ SM. Baro-VNAV and VDP NA when using Syracuse altimeter setting. Circling NA southwest of Rwy 15-33.

MISSED APPROACH: Climb to 3500 direct BOLTZ and hold.

ATIS 118.7	SYRACUSE APP CON 127.425 290.45	GRIFFISS TOWER ★ 118.1 (CTAF) 0 291.7	GND CON 121.9	UNICOM 122.95
----------------------	---	---	-------------------------	-------------------------



ELEV 504	D	TDZE 504
-----------------	----------	-----------------



4 NM Holding Pattern		TURYN		SCOUT		HOTSU 3 NM to RW15		3500	BOLTZ
3500		←327° →147°		147°		2500		* LNAV only	
GP 3.00° TCH 55		6.5 NM		3 NM		1.8 NM		*1.2 NM to RW15	
				*1500		RW15			
CATEGORY	A	B	C	D					
LPV DA	704-1		200 (200-1)						
LNAV/ VNAV DA	1052-2		548 (600-2)						
LNAV MDA	940-1 436 (500-1)		940-1¼ 436 (500-1¼)		940-1½ 436 (500-1½)				
CIRCLING	1140-1 636 (700-1)	1260-1 756 (800-1)		1400-2¾ 896 (900-2¾)		1640-3 1136 (1200-3)			