

LOC/DME I-BYW 110.9 Chan 46	APP CRS 091°	Rwy Idg TDZE 680 Apt Elev 680	ILS PRM Y RWY 10R (CLOSE PARALLEL) CHICAGO O'HARE INTL (ORD)
---	------------------------	---	---

RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
From GIBNS: RNAV-1 GPS required.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF Comm required.
See additional requirements on AAUP.

ALSIF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 133.0 348.0 PRM 128.05	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)	CLNC DEL 121.6	CPDLC
--	---	---	--	---	--------------------------	-------

MSA ORD 25 NM
3400

FERLL I-BYW [27.8] RADAR
MLSEN I-BYW [24.7] RADAR
OLLGA I-BYW [21.5] RADAR
LEATH I-BYW [18.4] RADAR
(IF) GOOZY I-BYW [15.3] RADAR
KVENN I-BYW [12.1] RADAR
FLYNT INT I-BYW [6.6] RADAR

271° 091°
8000 7000 6000 5000 4000 2300
(3.1) (3.1) (3.1) (3.1) (5.6)

9000 087° (20.1)
R-248 068° 248°

DUPAGE 108.4 DPA Chan 21

1468 883 1185 813 807

1130 Obk Chan 77
R-195

LOCALIZER 110.9 I-BYW Chan 46 LOC offset 2.50°

ALTERNATE MISSED APCH FIX
JOLIET 112.3 Chan 70
R-246 066° 246°

FERLL I-BYW [27.8] RADAR
MLSEN I-BYW [24.7] RADAR
OLLGA I-BYW [21.5] RADAR
GOOZY I-BYW [15.3] RADAR
LEATH I-BYW [18.4] RADAR
KVENN I-BYW [12.1] RADAR
FLYNT INT I-BYW [6.6] RADAR

9000 091°
8000 7000 6000 5000 4000 2300

GS 3.00° TCH 55

3.1 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM 5.6 NM 4.9 NM

CATEGORY A B C D

S-ILS 10R 930/24 250 (300-1/2)

ELEV 680 TDZE 680

HIRL all Rwys
TDZ/CL all Rwys except 4L

CHICAGO, ILLINOIS
Orig-D 22APR21

41°59'N-87°54'W

CHICAGO O'HARE INTL (ORD)
ILS PRM Y RWY 10R (CLOSE PARALLEL)