

WAAS

CH **82200**

W18A

APP CRS

185°

Rwy Idg

6107

TDZE

592

Apt Elev

592

RNAV (GPS) RWY 18

PRYOR FLD RGNL (DCU)

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Huntsville Intl-Carl T Jones Fld altimeter setting: increase LPV DA to 817 and LNAV/VNAV DA to 920 and all visibilities ½ mile. Increase all MDA 40 feet and LNAV Cat C and D visibility ⅓ mile. VDP and Baro-VNAV NA when using Huntsville Intl-Carl T Jones Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F).

MISSED APPROACH:

Climb to 3000 direct ATHEN and hold.

ASOS 118.375	HUNTSVILLE APP CON* 118.05 239.0	UNICOM 123.075 (CTAF) 0
------------------------	--	-----------------------------------

ELEV 592

TDZE 592

81

001 X 0019

636

36

3000 ATHEN

*LNAV only

RWY 18

ZADVI 1.8 NM to RWY 18

ATUYO 2200

ETEYV 4 NM Holding Pattern

GP 3.00° TCH 47

CATEGORY	A	B	C	D
LPV DA	792-¾		200 (200-¾)	
LNAV/VNAV DA	895-1		303 (400-1)	
LNAV MDA	980-1	388 (400-1)	980-1⅛	388 (400-1⅛)
CIRCLING	1040-1 448 (500-1)	1060-1 468 (500-1)	1340-2¼ 748 (800-2¼)	1340-2½ 748 (800-2½)

DECATUR, ALABAMA

Amdt 2 04FEB16

34°39'N-86°57'W

PRYOR FLD RGNL (DCU)

RNAV (GPS) RWY 18