

ILS PRM RWY 4R (CAT II & III)

(CLOSE PARALLEL)

DETROIT METRO WAYNE COUNTY (DTW)


LOC/DME I-DTW 110.7 Chan 44	APP CRS 036°	Rwy Idg TDZE Apt Elev	11494 640 645
---	------------------------	-----------------------------	--

RNAV 1-GPS. DME or RADAR required. CLEVR, CAATZ and ELDNN: RNAV 1-DME/DME/IRU or GPS required. Aircraft not DME/DME/IRU or GPS equipped- RADAR required for procedure entry.


Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF Comm required. See additional requirements on AAUP. Procedure NA when glideslope not available.

ALSF-2 MISSED APPROACH:
Climb to 4000 on DXO
VOR/DME R-035 to
LUPAY/DXO VOR/DME
15.6 DME and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 128.125 317.725 PRM 135.775	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	---	---	---------------------------	-------



BAANG I-DTW R-035 25 RADAR	JULEP I-DTW R-035 21.9 RADAR	CULOP I-DTW R-035 18.8 RADAR	HIMEX I-DTW R-035 15.6 RADAR	EVABE I-DTW R-035 12.5 RADAR	JELLY I-DTW R-035 9.3 RADAR	ETALE I-DTW R-035 6.2 RADAR	IM R-035 6.2 RADAR
8000	7000	6000	5000	4000	3000	2000	765
3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.1 NM	3.2 NM	4.1 NM	980'
CATEGORY	A	B	C	D			
S-ILS 4R		CAT II RA 104/12	100 DA 740				
S-ILS 4R		CAT III	RVR 06				



TDZ/CL Rwy 3R, 4L, 4R and 22R
REIL Rwy 3L, 9L, 9R and 21R
HIRL all runways