

WAAS CH 82241 W04D	APP CRS 036°	Rwy Idg 10000 TDZE 645 Apt Elev 645
--	------------------------	--

RNAV (GPS) Z RWY 4L

DETROIT METRO WAYNE COUNTY (DTW)

RNP APCH


Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.

ALSF-2



MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct DOHNT and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 135.0 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CLNC DEL 120.65	CPDLC
--------------------------	--	-------------------------------------	---	---------------------------	-------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).						1100 4000 DOHNT	
ASLII NATIY REGGE PAYED HIPKA 3000 036° 3000 3000 2000 2000 GP 3.00° TCH 55 *1260 *1.8 NM to RW04L *1 NM to RW04L RW04L *LNAV only.							