

APP CRS 320°	Rwy Idg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

ELEV 796 D TDZE 793

3000 KEADY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

BTTLR 2400

GP 3.00° TCH 53

See planview for multiple IF locations.

4.9 NM

CATEGORY	A	B	C	D
RNP 0.19 DA		1134/30	341 (400-%)	
RNP 0.30 DA		1196/45	403 (400-%)	

AUTHORIZATION REQUIRED

INDIANAPOLIS, INDIANA

Amtd 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32