


WAAS CH 78101 W16A	APP CRS 160°	Rwy Idg TDZE Apt Elev	7000 682 682
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 16
DRAUGHON-MILLER CENTRAL TEXAS RGNL (TPL)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 3600 direct FADXY and on track 074° to BARBA and hold, continue climb-in-hold to 3600.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cats C/D visibility to ⅞ SM.			

AWOS-3PT 134.975	GRAY APP CON 120.075 370.0	CLNC DEL 125.9	UNICOM 123.0 (CTAF)
----------------------------	--------------------------------------	--------------------------	-------------------------------



ELEV 682		TDZE 682
-----------------	--	-----------------



MIRL Rwy 3-21
MIRL Rwy 16-34

4 NM Holding Pattern		IHSAZ	IFDOH	3600	FADXY	tr 074°	BARBA
6000 ← 340°		3000 → 160°	2400	CUMIX 1.7 NM to RW16			
GP 3.00°		TCH 45	2400	0.7 NM to RW16			
			1260	RW16			
			6 NM	3.6 NM	1 NM	0.7	
CATEGORY	A	B	C	D			
LPV DA	882-½		200 (200-½)				
LNAV/VNAV DA	932-½		250 (300-½)				
LNAV MDA	960-½		278 (300-½)				
	1140-1	1200-1	1280-1½	1420-2¼			
	458 (500-1)	518 (600-1)	598 (600-½)	738 (800-2¼)			

SC-3, 15 MAY 2025 to 12 JUN 2025

SC-3, 15 MAY 2025 to 12 JUN 2025