

WAAS CH 82332 W36A	APP CRS 001°	Rwy Idg 4098 TDZE 572 Apt Elev 573
--	------------------------	---


RNAV (GPS) RWY 36

SALEM-LECKRONE (SLO)

▼ Baro-VNAV NA when using Centralia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). When local altimeter setting not received, use Centralia altimeter setting: increase LPV DA to 1045 feet and visibility ¼ SM; increase LNAV/VNAV DA to 1093 feet; increase all MDAs 40 feet and Circling Cats C/D visibility ¼ SM. Procedure NA at night. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 2600 direct EDHUJ and hold.

AWOS-3PT 118.525	KANSAS CITY CENTER 127.7 351.825	UNICOM 122.725 (CTAF) 0
----------------------------	--	-----------------------------------




2600 EDHUJ VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 28).

4 NM Holding Pattern

The holding pattern diagram shows the 2600 NoPT holding pattern and the 4 NM holding pattern. The chart includes various navigation aids such as the (FAF) OBDIW, (IAF) QAMKI, (IAF) NENUJ, and (IF/IAF) EMLIJ. The chart also shows the 2600 NoPT holding pattern and the 4 NM holding pattern. The chart includes various navigation aids such as the (FAF) OBDIW, (IAF) QAMKI, (IAF) NENUJ, and (IF/IAF) EMLIJ.

CATEGORY	A	B	C	D
LPV DA		1017-1½	445 (500-1½)	
LNAV/VNAV DA		1065-1¾	493 (500-1¾)	
LNAV MDA	1040-1	468 (500-1)	1040-1¾	468 (500-1¾)
CIRCLING	1040-1	467 (500-1)	1380-2¼ 807 (900-2¼)	1380-2½ 807 (900-2½)



EC-3, 15 MAY 2025 to 12 JUN 2025

EC-3, 15 MAY 2025 to 12 JUN 2025