

APP CRS
160°

Rwy Idg
TDZE
2377

Apt Elev
2377

RNAV (GPS) RWY 16

OZONA MUNI (OZA)

GPS or RNP-0.3 required. DME/DME RNP-0.3 NA. Procedure NA at night.

Obtain local altimeter on CTAF; when not received, use San Angelo altimeter setting.

Rwy 16 helicopter visibility reduction below ¼ SM NA.

MISSED APPROACH: Climb to 5000 direct IXALE WP and hold.

AWOS-3PT 118,425	HOUSTON CENTER 125.75 346.4	UNICOM 122.8 (CTAF) 0
----------------------------	---------------------------------------	---------------------------------

ELEV **2377**

TDZE **2377**

160° to RW16

9L

6003 X.75

0.43 UP

34

MIRL Rwy 16-34 0

IXALE

4300

160°

4200

3.05° TCH 50

1.6 NM

3.9 NM

6 NM

Procedure Turn NA

*VDP NA with San Angelo altimeter setting.

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 39).

*1.6 NM to RW16

5000

IXALE

MSA RW16 2.5 NM

4400

CATEGORY	A	B	C	D
LNAV MDA	2940-1¼ 563 (600-1¼)		2940-1½ 563 (600-½)	NA
CIRCLING	2980-1¼ 603 (700-1¼)		2980-1¾ 603 (700-¾)	NA
SAN ANGELO ALTIMETER SETTING MINIMUMS				
LNAV MDA	3180-1¼ 803 (800-1¼)		3180-2¼ 803 (800-¾)	NA
CIRCLING	3220-1¼ 843 (900-1¼)		3220-2½ 843 (900-½)	NA

OZONA, TEXAS

Orig-A 10SEP20

30°44'N-101°12'W

OZONA MUNI (OZA)

RNAV (GPS) RWY 16