



WAAS CH 86914 W18A	APP CRS 185°	Rwy Ldg TDZE 996 Apt Elev 1009
--	------------------------	--

RNAV (GPS) RWY 18
JAMES M COX DAYTON INTL (DAY)

RNP APCH.	MALSR 	MISSED APPROACH: Climb to 3000 direct GUPNE and track 255° to CAMMS and hold.
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cts visibility to RVR 4500. ** RVR 1800 authorized with use of FD or AP or HUD to DA.		

ATIS 125.8	COLUMBUS APP CON 134.45 323.15	DAYTON TOWER 119.9 257.7	GND CON 121.9	CLNC DEL 121.75
----------------------	--	------------------------------------	-------------------------	---------------------------



3000	GUPNE	tr 255°	CAMMS	
* LNAV only				
* 1.2 NM to RW18				
CATEGORY	A	B	C	D
LPV DA **	1196/24 200 (200-½)			
LNAV/VNAV DA	1274/24 278 (300-½)			
LNAV MDA	1420/24 424 (500-½)		1420/40 424 (500-¾)	
CIRCLING	1580-1 571 (600-1)		1580-1½ 571 (600-1½) 1640-2 631 (700-2)	