

ILS or LOC RWY 23R

LOC I-FFO 109.7	APCH CRS 233°	Rwy Idg 12,600 THRE 823 Arpt Elev 823
---------------------------	-------------------------	--

[USAF]

WRIGHT-PATTERSON AFB (KFFO)

DME or RADAR required for Localizer.

- ▼ *When ALS inop, increase RVR to 40 and vis to ¾ mile.
**When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
CAT CDE vis to 1¾ miles.

ALS-F1



† MISSED APPROACH: Climb via FFO R-233 to 2000, at 3 DME turn left direct CLACK to 3000 and hold.

ATIS 124.475 269.9	COLUMBUS APP CON 118.85 269.275	PATTERSON TOWER 127.8 281.45	GND CON 121.8 335.8
------------------------------	---	--	-------------------------------

*** When Rwy 23R VGSi inop, circling to Rwy 23R NA at night.

† Missed approach requires use of RNAV or ATC radar monitoring.

Autocoupled approach NA below 1458' MSL.

1290



PATTERSON
Chan 29 FFO

LOCALIZER 109.7
I-FFO



2049



1210



1299



985



1219



925



1024



1096



1467



AKATE



3



R-233



1400



1335



ANNEE RADAR



FFO 5.7



1033



2200



2000



FFO R-233



3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR

FFO 5.7

1033

2200

2000

FFO R-233

3

AKATE

3

1400

1335

ANNEE RADAR