

FORT WORTH, TEXAS

HI-TACAN Y RWY 18

TACAN NFW
Chan 24

APCH CRS
172°

Rwy ldg 11,999
TDZE 636
Arpt Elev 650

[USN]

FORT WORTH NAS JRB (CARSWELL FLD) (KNFW)

FUZ VORTAC or RADAR required.

* Circling not authorized E of Rwy 18-36.

MISSED APPROACH: Climb to 3000 direct LYLEE to intercept FUZ VORTAC R-218 to MOLKE and hold.

ATIS★
351.675

LONE STAR APP CON
125.8 257.95

NAVY FORT WORTH TOWER★
120.950 269.325

GND CON
121.675 279.575

CLNC DEL
126.4 254.325

ASR/
PAR

When local altimeter is not received use Fort Worth Meacham altimeter setting.

CAUTION: Intermediate length 5.4 NM less than minimum 6 NM for CAT C-E.

EMERG SAFE ALT 100 NM 4000

↑ VDP NA when using FTW altimeter setting

OLACK NFW 12

BUDGE NFW 6.6

FAMAL NFW 3

HIKDI NFW 1.4

3000

LYLEE

FUZ R-218

MOLKE FUZ 25

ELEV 650

TDZE 636

172°

REIL Rwy 18

HIRL Rwy 18-36

81

11,999 x 200

177

350 x 60

36

TWR

ASSAULT STRIP

CATEGORY	C	D	E
S-18	1100-1½	464 (500-1½)	
CIRCLING*	1320-1¾ 670 (700-1¾)	1340-2¼ 690 (700-2¼)	1440-2¾ 790 (800-2¾)
FORT WORTH MEACHAM ALTIMETER			
S-18	1120-1½	484 (500-1½)	
CIRCLING*	1340-2 690 (700-1)	1360-2¼ 710 (700-2¼)	1460-2¾ 810 (900-2¾)

FORT WORTH, TEXAS

32°46'N-97°26'W

FORT WORTH NAS JRB (CARSWELL FLD) (KNFW)

HI-TACAN Y RWY 18

SC-2, 12 JUN 2025 to 10 JUL 2025

SC-2, 12 JUN 2025 to 10 JUL 2025