

WAAS CH 69602 W10A	APP CRS 098°	Rwy Idg TDZE 198 Apt Elev 257	7000
--	------------------------	---	-------------

RNAV (GPS) RWY 10R

MONTEREY RGNL (MRY)

RNP APCH - GPS.

▼


⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C. Circling NA south of Rwy 10R-28L. For inop ALS, increase LPV all Cats visibility to 1½ SM and LNAV Cat C/D visibility to 2½ SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 5000 direct SNS VORTAC and hold, continue climb-in-hold to 5000.
*Misted approach requires minimum climb of 387 feet per NM to 1700.

ATIS 119.25	NORCAL APP CON 133.0 251.15 (001°-135°) 127.15 307.125 (136°-360°)	MONTEREY TOWER ★ 118.4 (CTAF) 0 257.8	GND CON 120.875 348.6	CLNC DEL 135.45	UNICOM 122.95
-----------------------	--	--	---------------------------------	---------------------------	-------------------------



ELEV 257

D

TDZE 198

4 NM Holding Pattern

ZEBED

MINCK

1000

5000

SNS

6000

2600

278°

098°

098°

1700

2.4 NM to RWY 10R

RWY 10R

GP 3.00° TCH 45

3.7 NM

2.3 NM

2.4 NM

CATEGORY	A	B	C	D
LPV DA*		398/24	200 (200-½)	
LPV DA		677/50	479 (500-1)	
LNAV/VNAV DA		754/60	556 (500-1¼)	
LNAV MDA	980/24 782 (800-½)	980/40 782 (800-¾)	980-1¾ 782 (800-1¾)	
CIRCLING	980-1 723 (800-1)	980-1¼ 723 (800-1¼)	1280-3 1023 (1100-3)	NA

098°

101

AS

1.4° UP

TWR 301

3503 X 50

7175 X 150

2810

28R

MIRL Rwy 10L-28R
HIRL Rwy 10R-28L
REIL Rwy 28L
REIL Rwy 10L and 28R