

WAAS
CH **82712**
W11A

APP CRS
112°

Rwy Idg **4808**
TDZE **1487**
Apt Elev **1497**

RNAV (GPS) RWY 11

EASTERN OREGON RGNL AT PENDLETON (PDT)

RNP APCH.

▼
⚠

Baro-VNAV and VDP NA when using Walla Walla altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Walla Walla altimeter setting and increase all DA/MDA 120 feet; VNAV all Cats visibility 1/8 SM, LNAV Cat C visibility 3/8 SM, and Cat D visibility 1/2 SM, Circling Cat C visibility 1/4 SM and Circling Cat D visibility 1/2 SM.

MISSED APPROACH:
Climb to 5000 direct
ADXAB and on track
007° to ZUTED and hold.

ASOS
118.325

SPOKANE APP CON ★
133.15 379.15

PENDLETON TOWER ★
119.7 (CTAF) 257.8

GND CON
121.9 257.8

UNICOM
122.95

5 NM

14000
4500

HOLD

5 NM

112°

(IAF) CORDO

4500 NoPT

078° (3.1)

4500 NoPT

004° (12.4)

(IAF) ECHOD

4500 NoPT

178° (11.6)

(IAF) GINLE

4500 NoPT

004° (12.4)

(IAF) ECHOD

3300

112°

(IF/IAF) PRUCE

4500

304°

(FAF) DRVIG

1611

1811

RW11

1611

1811

PENDLETON PDT

007°

(18.1)

ZUTED

5 NM

033°

213°

ZUTED

2610

A

6700

MSA RW11 25 NM

ELEV 1497

D

TDZE 1487

5 NM Holding Pattern

PRUCE

14000
4500

292°

112°

GP 3.00°
TCH 43

DRVIG

3300

112°

RW11

8 NM

4.5 NM

1 NM

5000

ADXAB

ZUTED

tr 007°

* LNAV only

* 1 NM to RW11

CATEGORY	A	B	C	D
LPV DA	1737-1 250 (300-1)			
LNAV/VNAV DA	1850-1¼ 363 (400-1¼)			
LNAV MDA	1860-1 373 (400-1)		1860-1¼ 373 (400-1¼)	
CIRCLING	1920-1 423 (500-1)	1960-1 463 (500-1)	1980-1½ 483 (500-1½)	2200-2¼ 703 (800-2¼)

REIL Rwy 11 and 29

MIRL Rwy 11-29

HIRL Rwy 8-26

NW-1, 12 JUN 2025 to 10 JUL 2025

NW-1, 12 JUN 2025 to 10 JUL 2025

PENDLETON, OREGON

Orig-A 15AUG19

EASTERN OREGON RGNL AT PENDLETON (PDT)

45°42'N-118°51'W

RNAV (GPS) RWY 11