

RNAV (GPS) RWY 10
SAVANNAH/HILTON HEAD INTL (SAV)

▼ For inop ALS increase LNAV/VNAV all Cats visibility to 1½ SM, increase LNAV Cat C/D to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Hilton Head Island altimeter setting and increase LPV DA to 296 feet and all visibilities to RVR 2000, increase LNAV/VNAV DA to 596 feet and all visibilities to 1¼ SM, increase all MDAs 80 feet and LNAV Cat C/D visibility to RVR 5000. For inop ALS when using Hilton Head Island altimeter setting, LNAV/VNAV all Cats visibility to 1½ SM, increase LNAV Cat C/D visibility to 1¾ SM. VDP and Baro-VNAV NA when using Hilton Head Island altimeter setting.



MISSED APPROACH:
Climb to 2500 direct
TELOE and hold.

[illegible]

CATEGORY	A	B	C	D
LPV DA	230/18 200 (200-½)			
LNAV/ VNAV DA	530/50 500 (500-1)			
LNAV MDA	440/24 410 (400-½)		440/40 410 (400-¾)	
 CIRCLING	520-1 470 (500-1)		740-2 690 (700-2)	740-2¼ 690 (700-2¼)

TDZ/CL Rwy 10
REIL Rwy 19 and 28 **L**
HIRL Rwy 1-19 and 10-28 **L**

SE-4, 12 JUN 2025 to 10 JUL 2025

SE-4, 12 JUN 2025 to 10 JUL 2025