



ATIS
120.825
CLNC DEL
120.125
CLNC DEL (when twr closed)
121.35
GND CON
120.125
SAN MARCOS TOWER★
126.825
AUSTIN DEP CON
119.0 370.85

**TOP ALTITUDE:
ASSIGNED BY ATC**

NOTE: RADAR required.
NOTE: DME/DME/IRU or GPS required.
NOTE: RNAV 1.

MUCKY



TAKEOFF MINIMUMS:

Rwys 8, 13, 17, 26: Standard.

Rwy 31: Standard with minimum climb of 210' per NM to 2600.

Rwy 35: Standard with minimum climb of 230' per NM to 2600.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 8: Climb on heading 081° or as assigned by ATC for vectors to cross PAYDA at or above 5000, thence....

TAKEOFF RUNWAY 13: Climb on heading 126° or as assigned by ATC for vectors to cross PAYDA at or above 5000, thence....

TAKEOFF RUNWAY 17: Climb on heading 171° or as assigned by ATC for vectors to cross PAYDA at or above 5000, thence....

TAKEOFF RUNWAY 26: Climb on heading 261° or as assigned by ATC for vectors to cross PAYDA at or above 5000, thence....

TAKEOFF RUNWAY 31: Climb on heading 306° or as assigned by ATC for vectors to cross PAYDA at or above 5000, thence....

TAKEOFF RUNWAY 35: Climb on heading 351° or as assigned by ATC for vectors to cross PAYDA at or above 5000, thence....

...on track 279° to MUCKY. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.